







Orion HD50

High-performance 5-inch stabilized EO/IR camera system for small unmanned vehicles

-  **MISSION PROVEN**
TRL 9 for military and commercial applications
-  **DIRECT DRIVE ARCHITECTURE**
Best-in-class robustness and stability
-  **EMBEDDED VIDEO PROCESSING**
Electronic stabilization and scene tracking
-  **ONBOARD GPS/INS**
Accurate real-time vehicle and target location
-  **VISIBLE AND THERMAL CAMERAS**
Day and night operations with a single payload
-  **ITAR FREE**
Non-controlled configurations available
-  **720P HD DIGITAL VIDEO**
Fully digital, h.264-compliant video pipeline
-  **ENVIRONMENTALLY SEALED**
Highly resistant to dust and water
-  **NVG-COMPATIBLE LASER POINTER**
850nm laser for precise and discreet pointing
-  **ETHERNET INTERFACE**
Video and gimbal control over ethernet or RS-232
-  **METADATA**
Target location, gimbal health, and more

SOFTWARE

FEATURES

- Onboard h.264 compression with adjustable bitrate
- Dynamic or static IP addressing
- Field upgradable software
- Onboard electronic stabilization
- Onboard scene tracking
- MISB-compliant output including embedded KLV metadata
- Optional target tracking

GPS/INS

- IMU co-located with cameras
- 1.5° (typical) total system accuracy with optional 0.5° upgrade
- Real time geointing and geolocation
- Attitude, velocity and position computed at 200Hz
- Onboard GPS receiver
- GPS and heading accepted over serial or Ethernet
- Dual GPS heading support

ELECTRICAL

- Control over Ethernet or serial
- Ethernet and analog video
- 15W average, 100W peak power consumption
- 10V to 30V input voltage
- Interface connector: 51 pin micro-D connector conforming to MIL-DTL-83513
- GPS connector: SMA
- Analog video connector: SMA
- GPS antenna: 3.3V active, L1 band

MECHANICAL

- Weight: 1700g - 2100g
- Glass and Germanium windows
- Direct drive brushless motors
- 0.02° encoder resolution
- 60Hz closed loop stabilization bandwidth
- 100μRAD - 200μRAD RMS jitter



HD50-MV

CAMERA CONFIGURATIONS

CONFIGURATION	WEIGHT	CAMERAS	VISIBLE FOV	THERMAL FOV
HD50-XV	1700g	720p Global Shutter Visible Camera	60°-2.1° Digital to 1.0°	—
HD50-LV	2000g	720p Global Shutter Visible Camera FLIR Boson 640 with 36mm lens	60°-2.1° Digital to 1.0°	12.2° Digital to 3.1°
HD50-LV-CZ	2000g	720p Rolling Shutter Visible Camera FLIR Boson 640 with 15-75mm lens	17.4°-5.1° Digital to 1.8°	29°-5.9° Digital to 3.0°
HD50-MV	2100g	720p Rolling Shutter Visible Camera Cooled MWIR with 25-175mm lens	17.4°-5.1° Digital to 1.8°	17.5°-2.5° Digital to 1.3°